Application No.: 10/619,891 Docket No.: NONY 3.0-004

## IN THE CLAIMS

1-47 (canceled)

48. (new) A cosmetic receptable comprising: a body containing a cosmetic; and

a neck attached to said body, said neck including a first portion having a first diameter and having first fixing means, and a second portion located between said body of said receptacle and said first portion, said second portion having a second diameter greater than said first diameter, and having second fixing means.

- 49. (new) The receptacle according to claim 48, wherein said neck includes a shoulder connecting said first portion to said second portion.
- 50. (new) The receptacle according to claim 49, wherein said shoulder includes a plane annular surface extending outside said neck, said shoulder being perpendicular to said neck.
- 51. (new) The receptacle according to claim 48, wherein at least one of said first portion of said neck or said second portion of said neck includes a thread.
- 52. (new) The receptacle according to claim 51, wherein both said first fixing means and said second fixing include threads and wherein said threads enable screw fastening by turning in the same direction.
- 53. (new) The receptacle according to claim 48, wherein at least one of said first fixing means and said second fixing means includes at least one snap-fastening member.
- 54. (new) The receptacle according to claim 53, wherein said snap-fastening member includes an annular bead.
- 55. (new) The receptacle according to claim 48, wherein said receptacle comprises a plastic material.
- 56. (new) The receptacle according to claim 48, wherein said first portion has a first inside diameter and said

second portion has a second inside diameter greater than said first inside diameter.

- 57. (new) The receptacle according to claim 48, wherein said neck includes an inside shoulder connecting said first portion to said second portion.
  - 58. (new) A kit comprising:

a receptacle as defined in claim 48; and at least one accessory configured for removably fixing onto said neck of said receptacle.

- 59. (new) The kit according to claim 58, wherein said accessory cooperates with said second portion of said neck.
- 60. (new) The kit according to claim 58, wherein said neck includes a shoulder connecting said first portion to said second portion and said accessory includes an assembly skirt which cooperates with said second portion, said assembly skirt including a sealing surface that abuts said shoulder when fixed to said neck.
- 61. (new) The kit according to claim 60, wherein said sealing surface comprises an annular bead.
- 62. (new) The kit according to claim 60, wherein said accessory does not include a sealing lip that abuts an inside of said neck of said receptacle.
- 63. (new) The kit according to claim 58, wherein said accessory includes an applicator.
- 64. (new) The kit according to claim 63, wherein said applicator includes teeth.
- 65. (new) The kit according to claim 64, wherein at least one of said teeth includes at least one dispenser orifice.
- 66. (new) The kit according to claim 65, wherein said at least one dispenser orifice is displaced from the free end of said at least one of said teeth.

Docket No.: NONY 3.0-004

The kit according to claim 66, wherein 67. (new) said at least one dispenser orifice substantially limits a cosmetic to be dispensed from dispensing other than between said teeth.

- The kit according to claim 63, wherein 68. (new) said applicator includes at least one row of teeth including a pair of end teeth located at the respective ends of said at least one row of teeth, said pair of end teeth having dispenser orifices which face others of said at least one row of teeth.
- The kit according to claim 63, wherein 69. (new) said applicator includes at least one row of teeth including a pair of end teeth located at the respective ends of said at least one row of teeth, said end teeth have no dispenser orifices.
- The kit according to claim 68, wherein 70. (new) at least one tooth of said row of teeth located between said pair of end teeth includes a plurality of said dispenser orifices on the exterior of said at least one tooth such that said plurality of dispenser orifices are parallel to said at least one row of teeth.
- The kit according to claim 70, wherein 71. (new) said plurality of dispenser orifices are located on opposite sides of said at least one tooth.
- 72. The kit according to claim 70, wherein (new) all of said teeth located between said pair of end teeth include at least one dispenser orifice.
- The kit according to claim 65, wherein (new) said at least one of said teeth includes a groove extending from a free end of said at least one of said teeth to said at least one dispenser orifice.
- The kit according to claim 64, wherein 74. said applicator includes at least six teeth, each of said teeth including at least one dispenser orifice.

75. (new) The kit according to claim 64, wherein said teeth are of substantially the same length.

- 76. (new) The kit according to claim 63, wherein said applicator is made by molding.
- 77. (new) The kit according to claim 58, wherein at least one of said first fixing means and said second fixing means includes a thread, said kit having at least one accessory adapted for screwing onto said thread.
- 78. (new) The kit according to claim 58, wherein at least one of said first fixing means or said second fixing means comprises at least one snap-fastening member, said kit including at least one accessory arranged with at least one complementary snap-fastening member suitable for cooperating with at least one said snap-fastening member.
- 79. (new) The kit according to claim 58, including at least two accessories of different kinds.
- 80. (new) The kit according to claim 79, wherein said first of said two accessories is adapted for cooperating with said first portion of said neck and said second of said two accessories is adapted for cooperating with said second portion of said neck.
- 81. (new) The kit according to claim 79, wherein the first of said two accessories includes a cap and said second of said two accessories comprises an applicator.
- 82. (new) The kit according to claim 79, wherein at least one of said at least two accessories cooperates with said first portion of said neck.
- 83. (new) The kit according to claim 82, wherein said at least one accessory is selected from the group consisting of a cap, an endpiece, and a receptacle.
- 84. (new) The kit according to claim 58, wherein said receptacle is filled with a cosmetic.

Application No.: 10/619,891

- 85. (new) The kit according to claim 85, wherein said cosmetic comprises a substance for coloring the hair.
- 86. (new) An applicator for removably affixing to a neck of a receptacle having a neck, said applicator including an assembly skirt having a free end and including an annular bead displaced from said free end of said applicator and on an inside surface of said assembly skirt.
- 87. (new) The applicator according to claim 86, further comprising screw means for screw fastening said applicator on said neck of said receptacle.
  - 88. (new) A receptacle comprising:

a body; and

a neck providing an opening into said body, said neck including a first portion having a first diameter and having a first fixing means, and a second portion located between said body and said first portion, said second portion having a second diameter greater than said first diameter, and having second fixing means, said neck including an inside shoulder connecting said first portion to said second portion.

- 89. (new) A receptacle comprising:
  - a body; and

a neck providing an opening into said body, said neck including a first portion having a first diameter and having a first thread, and a second portion located between said body and said first portion, said second portion having a second diameter greater than said first diameter and having a second thread, said first and said second threads enabling screw fastening in the same direction.

- 90. (new) A receptacle comprising:
  - a body; and

a neck providing an opening into said body, said neck including a first portion having a first diameter, and including at least one first fixing means selected from the

group consisting of a first thread or first snap-fastening means, and a second portion located between said body and said first portion, said second portion having a second diameter greater than said first diameter, and including at least one second fixing means selected from the group consisting of a second thread or second snap-fastening means.

## 91. (new) A kit comprising:

1

a receptable including a body and a neck providing an opening into said body, said neck including a first portion having a first diameter and including a first fixing means, and a second portion located between said body and said first portion, said second portion having a second diameter greater than said first diameter, and having second fixing means; and

at least two accessories adapted for attachment to said neck.

92. (new) The kit according to claim 91, wherein said at least two accessories are selected from the group consisting of an applicator, an endpiece, a cap, and a second receptacle.

## 93. (new) A kit comprising:

a receptable including a body and a neck providing an opening into said body, said neck including a first portion having a first diameter and including first fixing means, and a second portion located between said body and said first portion, said second portion having a second diameter greater than said first diameter, and having second fixing means; and

at least two accessories for cooperating with said first portion and said second portion, respectively.

94. (new) The kit according to claim 93, wherein said at least two accessories are selected from the group

consisting of an applicator, an endpiece, a cap, and a second receptacle.

- 95. (new) The receptacle according to claim 47, wherein said neck defines an opening into said body.
  - 96. (new) A receptacle comprising:

a body; and

a neck providing an opening into said body, said neck including a first portion having a first inside diameter and having a first fixing means and a second portion located between said body of said receptacle and said first portion, said second portion having a second inside diameter and a second fixing means, wherein said second inside diameter is greater than said first inside diameter.